

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures
 Product name : Unleaded Injector Cleaner
 Product code : MT-153

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : FOLLOW LABEL DIRECTIONS

1.3. Details of the supplier of the safety data sheet

THE MASTERS TOUCH
 20000 Plum Canyon Rd 1721
 Santa Clarita, CA 91350
 Tell: +1661-510-1830

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 4 H227
 Acute Tox. 4 (Inhalation:dust,mist) H332
 Skin Irrit. 2 H315
 STOT SE 3 H335

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS08

GHS02

Hazard statements (GHS-US) : H350 - May cause cancer
 H227 - Combustible liquid
 H315 - Causes skin irritation
 H302+H332 - Harmful if swallowed or if inhaled

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
 P202 - Do not handle until all safety precautions have been read and understood
 P280 - Wear protective gloves/protective clothing/eye protection/face protection
 P308+P313 - IF exposed or concerned: Get medical advice/attention
 P405 - Store locked up
 P501 - Dispose of contents/container to ...

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification (GHS-US)
distillates (petroleum), sweetened middle	(CAS No) 64741-86-2	29.9 - 37.30025	Carc. 1A, H350
POLYETHER AMINE	(CAS No) Confidential	22.425 - 29.82525	Flam. Liq. 4, H227
distillates, hydrotreated light	(CAS No) 64742-47-8	10 - 30	Asp. Tox. 1, H304
naphtha, heavy aromatic	(CAS No) 64742-94-5	0.7475 - 3.66275	Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
N-phenylbenzenamine, reaction products with 2,4,4-trimethylpentene	(CAS No) 68411-46-1	1.3125 - 1.75	Skin Irrit. 2, H315

Name	Product identifier	%	Classification (GHS-US)
naphthalene	(CAS No) 91-20-3	< 1	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
diphenylamine	(CAS No) 122-39-4	< 0.0175	Skin Irrit. 2, H315 Eye Irrit. 2B, H320

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see ... on this label).
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause respiratory irritation.
- Symptoms/injuries after skin contact : Causes skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Unsuitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray.
- Hygiene measures : Wash ... thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.

Incompatible products : Strong bases. strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters

diphenylamine (122-39-4)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear approved mask.

Other information : When using, do not eat, drink or smoke.

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : Colourless to light yellow. Colorless.

Odor : characteristic.

Odor threshold : No data available

pH : No data available

Relative evaporation rate (butyl acetate=1) : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

: > 68.3 °C

Self ignition temperature : No data available

: No data available

Flammability (solid, gas) : No data available

Vapor pressure : No data available

Relative vapor density at 20 °C : No data available

Relative density : 0.814

Solubility : No data available

Log Pow : No data available

Log Kow : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity
10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled.

naphtha,heavy aromatic (64742-94-5)	
LD50 oral rat	> 5000 mg/kg (Rat)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (Rat)

naphthalene (91-20-3)	
ATE (oral)	500.000 mg/kg body weight

N-phenylbenzenamine, reaction products with 2,4,4-trimethylpentene (68411-46-1)	
LD50 oral rat	> 500 mg/kg (Rat)
LD50 dermal rat	> 2000 mg/kg (Rat)

Skin corrosion/irritation : Causes skin irritation.
 Serious eye damage/irritation : Not classified
 Respiratory or skin sensitization : Not classified
 Germ cell mutagenicity : Not classifiedBased on available data, the classification criteria are not met
 Carcinogenicity : Not classified
 Reproductive toxicity : Not classifiedBased on available data, the classification criteria are not met
 Specific target organ toxicity (single exposure) : May cause respiratory irritation.
 Specific target organ toxicity (repeated exposure) : Not classifiedBased on available data, the classification criteria are not met
 Aspiration hazard : Not classifiedBased on available data, the classification criteria are not met
 Potential Adverse human health effects and symptoms : Harmful if inhaled.
 Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause respiratory irritation.
 Symptoms/injuries after skin contact : Causes skin irritation.

SECTION 12: Ecological information

12.1. Toxicity

naphtha,heavy aromatic (64742-94-5)	
LC50 fish 1	2.1 - 4.2 mg/l (96 h; Lepomis macrochirus; Fresh water)
EC50 Daphnia 1	0.95 mg/l (48 h; Daphnia magna)
LC50 fish 2	2.34 mg/l (96 h; Oncorhynchus mykiss)
Threshold limit algae 1	1 mg/l (72 h; Skeletonema costatum; GROWTH)

N-phenylbenzenamine, reaction products with 2,4,4-trimethylpentene (68411-46-1)	
LC50 fish 1	> 47 mg/l (96 h; Brachydanio rerio; MEASURED CONCENTRATION)
LC50 fish 2	920 mg/l (96 h; Brachydanio rerio; NOMINAL CONCENTRATION)

diphenylamine (122-39-4)	
LC50 fish 1	> 20 mg/l (48 h; Leuciscus idus)
EC50 Daphnia 1	2.3 mg/l (24 h; Daphnia magna)
LC50 fish 2	2.2 - 5.1 mg/l (48 h; Oryzias latipes)
Threshold limit other aquatic organisms 1	1000 mg/l (24 h; Pseudomonas fluorescens)

12.2. Persistence and degradability

FUEL POWER-2	
Persistence and degradability	Not established.

distillates (petroleum), sweetened middle (64741-86-2)	
Persistence and degradability	Not established.
naphtha,heavy aromatic (64742-94-5)	
Persistence and degradability	Not readily biodegradable in water.
naphthalene (91-20-3)	
Persistence and degradability	May cause long-term adverse effects in the environment.
POLYETHER AMINE (Confidential)	
Persistence and degradability	Not established.
N-phenylbenzenamine, reaction products with 2,4,4-trimethylpentene (68411-46-1)	
Persistence and degradability	Not readily biodegradable in water. Photolysis in the air.
diphenylamine (122-39-4)	
Persistence and degradability	Not readily biodegradable in water.
ThOD	2.39 g O ₂ /g substance

12.3. Bioaccumulative potential

FUEL POWER-2	
Bioaccumulative potential	Not established.
distillates (petroleum), sweetened middle (64741-86-2)	
Bioaccumulative potential	Not established.
naphtha,heavy aromatic (64742-94-5)	
Log Pow	2.9 - 6.1
Bioaccumulative potential	Bioaccumable.
naphthalene (91-20-3)	
Bioaccumulative potential	Not established.
POLYETHER AMINE (Confidential)	
Bioaccumulative potential	Not established.
N-phenylbenzenamine, reaction products with 2,4,4-trimethylpentene (68411-46-1)	
Log Pow	4.64 (Experimental value)
Bioaccumulative potential	Not established.
diphenylamine (122-39-4)	
BCF fish 1	51 - 253 (Cyprinus carpio; TEST DURATION: 8 WEEKS)
Log Pow	3.22 - 3.50
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

diphenylamine (122-39-4)	
Surface tension	0.03 N/m (60 °C)
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations
13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
 Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / ADN R / IMDG / ICAO / IATA

US DOT (ground): NA1993, Combustible liquid, n.o.s., 3, III, Limited Quantity
 ICAO/IATA (air): NOT REGULATED,
 IMO/IMDG (water): NOT REGULATED,
 Special Provisions: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
 T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)
 T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
 TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

14.2. UN proper shipping name

DOT Proper Shipping Name : Combustible liquid, n.o.s.
 Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
 Packing group (DOT) : III - Minor Danger
 DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
 T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)
 T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
 TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
 DOT Packaging Exceptions (49 CFR 173.xxx) : 150
 DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
 DOT Packaging Bulk (49 CFR 173.xxx) : 241

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
 DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L

SECTION 15: Regulatory information

15.1. US Federal regulations

FUEL POWER-2	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
naphthalene (91-20-3)	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard

15.2. International regulations

CANADA

naphthalene (91-20-3)	
WHMIS Classification	Class B Division 4 - Flammable Solid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

15.2.2. National regulations

No additional information available

15.3. US State regulations

naphthalene (91-20-3)
U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List

SECTION 16: Other information

Indication of changes : Revision - See : *

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Carc. 2	Carcinogenicity Category 2
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 2 Moderate Hazard



Physical : 0 Minimal Hazard

SDS US (GHS HazCom 20) - Technical Chemical

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product