

MT-22

Fabric and Leather Coating

MATERIAL SAFETY

DATA SHEET

SECTION#1 Company and Product Identification

20000 Plum Canyon Rd #1721 Santa Clarita, CA 91350 661-510-1830

PART NO: MT33661 PAGE: 1

EFFECTIVE DATE: 10/27/19 DATE PREPARED: 09/06/19

This Material Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this MSDS must be given to the buyer or the information incorporated in your MSDS.

This MSDS complies with 29 CFR 1910.1200 (The Hazard Communication Standard)

ALIPHATIC HYDROCARBON * PEL: 500 PPM....
CAS #: Proprietary TLV: 50 PPM

CUSTOMER'S MATERIAL PEL: NOT AVAILABLE CAS #: NOT AVAILABLE TLV: NOT AVAILABLE

HYDROCARBON PROPELLANT PEL: 800 PPM CAS #: TLV: 800 PPM

"*" If present, IARL, NTP and OSHA carcinogens and chemical subject to this reporting requirements of SARA TITLE III, SECTION 313 are identified in

HAZARDOUS DECOMPOSITION PRODUCTS: None

Primary Routes entry: Inhalation, Eyes, Skin



GENERAL:

This material is an aspiration hazard and defects the skin. Breathing vapors of high concentrations may cause CNS depression.

EYE CONTACT:

Flush eyes with large amounts of water until irritation subside. If irritation persists, get medical attention.

SKIN CONTACT: Flush with large amounts of water; use soap it available. Remove grossly contaminated clothing, including shoes, and launder before reuse.

INHALATION: Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention INGESTION: If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

PRECAUTIONS

SPECIAL PRECAUTIONS: Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

PERSONAL PROTECTION:

For open systems where contact is likely, wear safety glasses with side shields, long sleeves, and chemical resistant gloves. Where concentrations in air may exceed the limits, work practice or other means of exposure reduction are not adequate, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.

========= SECTION#5 Fire Fighter Measures

======= PRODUCT DESCRIPTION: 10.5 OZ AERO

D.O.T. PROPER SHIPPING NAME: ORM-D CONSUMER COMMODITY

NFPA CODES: HEALTH - 1 FLAMMABILITY - 3 CORROSIVE - 0 REACTIVITY - 0

FIRE FIGHTING:

Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boiling over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.



MT-22

Fabric and Leather coating

===SECTION#6 ACCIDENTAL RELEASE MEASURES =======

High vapor/aerosol concentrations (greater than approximately 100 ppm) are irritating to the eyes and the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

======= SECTION#7 - HANDLING AND STORAGE ===============

Remove grossly contaminated clothing, including shoes, and launder before reuse.

VENTILATION: The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures or is agitated.

(PROPOSITION 65):SEC05

State of California SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 **WARNING:** IN ACCORDANCE WITH PROP 65, THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH

DEFECTS AND OTHER REPRODUCTIVE HARM

HANDLING STORAGE AND DECONTAMINATION PROCEDURES: When utilizing containers Follow standard safety practices for handling chemicals.

STEPS TO BE TAKEN IN CASE CONTAINER IS PUCTURED AND MATERIAL IS RELEASED: Clean up area by mopping or with absorbent materials and place in closed container for disposal. Consult Federal, State, and local Disposal authorities

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the Product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing.

Standard work shoes; discard if shoes cannot be decontaminated. Store contaminated clothing in well ventilated cabinets or closed Containers Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.



SECTION#8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

SKIN CONTACT: Low order of toxicity. Frequent or prolonged contact may

INHALATION:

High vapor/aerosol concentrations (greater than approximately 100 ppm) are irritating to the eyes and the respiratory tract may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. High vapor/aerosol concentrations (greater than approximately 100 ppm) are irritating to the eyes and the respiratory tract may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

INGESTION: Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe Pulmonary injury, possibly minimal toxicity.

VENTILATION REQUIREMENT: Use adequate level exhausts ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA

SECTION#9 PhysicalProperties

FLASH POINT (N/D): LEVEL 3 AEROSOL

EXPLOSIVE LIMIT (PRODUCT): LOWER - N/D UPPER - N/D

BOILING POINT FOR PRODUCT: NOT DETERMINED

VAPOR PRESSURE FOR PRODUCT: < 80 psi @ 65 deg F.

VAPOR DENSITY FOR PRODUCT: NOT DETERMINED

SPECIFIC GRAVITY: liquid 0.70 - 0.79

V.O.C. (GRAMS PER LITER): NOT DETERMINED

WATER SOLUBILITY: NIL

APPEARANCE: CLEAR COATING

EYE CONTACT: Slightly irritating but does not injure eye tissue.

======= SECTION#10 REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Temperatures above 130 degree F.

HAZARDOUS POLYMERIZATION: Will not occur

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing

agents

HAZARDOUS DECOMPOSITION PRODUCTS: None



====== SECTION#11 Toxicological Information

======== Low order of toxicity. Frequent or prolonged contact may

Irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

SECTION#14 Transport Info

Department of Transportation regulation: USA DOT not regulated.

Act, as applicable. This product was manufactured at the location identified on the MSDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above mentioned regulation.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.